

# ULTRASEAL ACRYLIC



**ULTRA  
SEAL**  
THE WATERPROOFING CHOICE



Weather  
Resistant



Durable &  
Flexible



UV  
Stable

UltraSeal Acrylic is a single component, water based, acrylic water proofing coating.

*Manufactured by NUI – Member of the RIGIFoam Group*

# ULTRASEAL ACRYLIC



**UltraSeal Acrylic** is a single component, water based, acrylic water proofing coating. The acrylic backbone resin increases adhesion and provides long-term colour stability. The product cures into a durable, flexible, UV stable and weather resistant film and is suitable for outdoor applications.

## APPLICATION

- Coatings can be applied by means of brush, roller or spray (single component airless or conventional spray equipment).
- UltraSeal Acrylic should be well mixed before use. Apply the first coat at a rate of 0.95 m<sup>2</sup>/litre and allow to dry. Apply the second coat after 24 hours.

## FILM DRYING TIME

The rate of cure is dependent on material and substrate temperature and relative humidity. High temperatures and humidity will accelerate the cure. Thicker films will take longer to cure.

Do not apply UltraSeal Acrylic under rainy conditions. UltraSeal Acrylic should be resistant to light rainfall after 6 hours, depending on ambient conditions.

## COLOURS



±24 HRS



WEATHERABLE

±24 HRS







TRAFFICABLE

±10 YRS



LIFESPAN

TOUCH DRY	FULL CURE	OVER-COATING	AVERAGE COVERAGE
			
± 3 hours	24 hours	3 - 12hours	± 0,95m <sup>2</sup> / per litre

## APPLICATION METHODS



Manufactured by NUI – Member of the RIGIFoam Group

[www.ultraseal.co.za](http://www.ultraseal.co.za)  
[www.rigifoam.co.za](http://www.rigifoam.co.za)  
+27 (0)11 421 0313



DISAVOWAL: The customer acknowledges and understands that after delivery, the goods will have left the control of Rigifoam (Pty) Ltd, and that the customer will be responsible for the unpacking of and connection/installation of the goods. The customer acknowledges that it is his/her further responsibility to ensure that a fully qualified and competent person is used to install the goods to ensure their effective operation. Failure by the customer to ensure the installation of the goods, according to the written instructions of the manufacturer and/or supplier, by a fully qualified and competent person, may result in the failure of the goods, injury, loss or damages to the customer. Accordingly, and in this event, Rigifoam (Pty) Ltd accepts no responsibility for any loss or damages that might arise by reason of death or personal injury to any person engaged in the installation or use of the goods thereafter, subject to the provisions of the Consumer Protection Act 68 of 2008.